

General instructions for cleaning and care























no.4 Rubber studs

**cleaning system without treatment
end of construction**

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

	cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	 dry vacuum cleaning			Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /			
1	 vacuum sweeping sweeping				Speedmatic Twister Turbo Sweep	large areas: <table border="1" data-bbox="1993 590 2072 662"><tr><td>2</td></tr><tr><td>m</td></tr></table>	2	m
2								
m								
2	 dusting damp mopping	Fit	100%	Mop/	Balit Varifix/ Balit/			
cleaning without maintenance care product (if coating follows)								
3	 wet scrubbing and wet vacuuming	Antiwax forte Antiwax	30 - 50% 10 - 30%	 Microsol fibre pad/  Scrubbing brush washbeton/	Monomatic LS / Watertank Duovac /	  		
3	 scrubber drying indirect method	Antiwax forte Antiwax	30 - 50% 10 - 30%	 Microsol fibre pad/  Scrubbing brush washbeton/  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	  		
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)								
4	 scrubber drying direct method	Redur	3%	 Microsol fibre pad/  Scrubbing brush washbeton/  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	without protective treatment		

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: repeat until separating agent is completely removed

General instructions for cleaning and care

no. 4 Rubber studs



maintenance cleaning

object _____

date _____






















address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

	cleaning method	frequency	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	 dry vacuum cleaning	<input type="checkbox"/>			Dust roller nozzle	Monovac / Scuba		
1	 vacuum sweeping	<input type="checkbox"/>				Speedmatic Twister Turbo Sweep	large areas: <table border="1" data-bbox="1989 555 2069 628"><tr><td>2 m</td></tr></table>	2 m
2 m								
1	 dusting damp mopping	<input type="checkbox"/>			Synthetic fur	Balit Varifix/ Balit/		
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed 	
cleaning without maintenance								
3	 wet mopping direct method	<input type="checkbox"/>	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drewell Variwet / B. Varifix		
3	 scrubber drying direct method	<input type="checkbox"/>	Ecofloor Reshine Liberio	0.5 - 1% 1 - 2% 0.5 - 3%	 Microsol fibre pad/  Scrubbing brush washbeton/  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic		
3	 polishing, vacuum polishing	<input type="checkbox"/>			B  Microsol fibre pad/  Polishing brush Union/	Monomatic HS / Suction ring Monom Monomatic DS /	after polishing 	
cleaning with maintenance								
3	 wet mopping direct method	<input type="checkbox"/>	Redur	1%	Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drewell Balit Varifix/		
3	 scrubber drying direct method	<input type="checkbox"/>	Redur	1%	 Microsol fibre pad/  Scrubbing brush washbeton/  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic		

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no. 4 Rubber studs



interim cleaning

object _____

date _____

















address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

	cleaning method	frequency	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			Synthetic fur	Balit Varifix/ Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			Dust roller nozzle	Monovac / Scuba	
1	 vacuum sweeping sweeping	<input type="checkbox"/>				Speedmatic Twister Turbo Sweep	large areas: <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed <input type="checkbox"/>
cleaning without maintenance							
3	 wet mopping indirect method	<input type="checkbox"/>	Reshine G Rewit 2000	3 - 5% 2 - 5%	Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drowell	 
3	 scrubber drying indirect method	<input type="checkbox"/>	Reshine G Rewit 2000 V Indumat	3 - 5% 2 - 5% 2 - 5%	 Microsol fibre pad/  Scrubbing brush washbeton/  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	 
3	 polishing, vacuum polishing	<input type="checkbox"/>			B  Microsol fibre pad/  Polishing brush Union/	Monomatic HS / Suction ring Monom Monomatic DS /	after polishing <input type="checkbox"/>

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care



no. 4 Rubber studs

basic cleaning

object _____

date _____

























address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

cleaning method	frequency	recommendations * chemical products dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping	<input type="checkbox"/>		Synthetic fur	Balit Varifix/ Balit/	
1  dry vacuum cleaning	<input type="checkbox"/>		S V Dust roller nozzle Dust roller nozzle	Monovac / Scuba	
2  chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek 100%			if needed 
cleaning without maintenance					
3  wet scrubbing and wet vacuuming	<input type="checkbox"/>	B Relino 20 - 50% G Rewit 2000 10 - 20% V Antiwax forte 30 - 50%	 Microsol fibre pad/  Scrubbing brush washbeton/	Monomatic LS / Watertank Duovac /	  
3  scrubber drying indirect method	<input type="checkbox"/>	B Relino 20 - 50% G Rewit 2000 10 - 20% V Antiwax forte 30 - 50%	 Microsol fibre pad/  Scrubbing brush washbeton/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	   
4 rinsing   	<input type="checkbox"/>	pure water	 Microsol fibre pad/  Scrubbing brush washbeton/	Monomatic LS / Duovac / Duomatic / Laser	 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: change pad often
Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.
When white abrasion occurs, carry out a full clean to remove all the protective coating
For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care

no. 4 Rubber studs



protective treatment

object _____

date _____
















address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

cleaning method	recommendations * chemical products dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting  damp mopping		Synthetic fur	Balit Varifix/ Balit/	
coating				
2  coating	Mepol HM Stoner 100%	Cover for Florfix ☉ Shampooing brush/	Florfix/ Monomatic LS /	1 - 3 thin layers  
2  waxing	Polish 100%	Cover for Florfix ☉ Shampooing brush/	Florfix/ Monomatic LS /	1 - 3 thin layers  
buffing wax treatment (only if necessary)				
3  dusting  damp mopping		Synthetic fur	Balit Varifix/ Balit/	
4  polishing, vacuum  polishing		C  Pad yellow/ C  Polishing brush Union/	Monomatic HS / Suction ring Monon Monomatic DS /	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

if needed

Do not coat floors with PUR coating provided in the factory

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use

Process treatment of protection: see description of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care


no. 4 Rubber studs



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Rubber-studded floor coverings are sensitive to strong alkalines such as soft soap and basic cleaners. Colour change: material damage!

Rubber-studded floor coverings are sensitive to certain solvents such as ketone and ester.

Fat-soluble colorants such as shoe polish or asphalt can penetrate into rubber-studded floor coverings: diffusion
Mould-release agents from production (silicone or paraffin-based) must be completely removed before basic treatment.
Paraffin-like antioxidants can migrate to the surface over time and form white clouds. These can be polished out.
Rubber-studded floor coverings with low studs can be spray cleaned.



Rubber-studded floor coverings are a blend of synthetic and natural rubber, sulphur (vulcanising agent), fillers and colour pigments.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: the needle penetrates only slightly, typical rubber smell, no crater formation.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.info@wetrok.ch, www.wetrok.ch, www.wetrok.com