


# General instructions for cleaning and care

no.26  Ceramic tiles, unglazed, clay paving stones, clinker brick





















**cleaning system without treatment  
end of construction**

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1  dry vacuum cleaning			<b>Dust roller nozzle</b> <b>Neverclog filter without ring</b> <b>Filter bag with ring</b>	<b>Twinvac /</b> Duovac / Silento /		
1  vacuum sweeping sweeping				<b>Speedmatic Twister</b> Turbo Sweep	large areas: <table border="1" data-bbox="1993 582 2072 654"><tr><td>2 m</td></tr></table>	2 m
2 m						
2  dusting damp mopping			<b>Masslinn 2000/Floorwit white</b>	<b>Balit Varifix/</b> Balit/		
<b>cleaning without maintenance care product (if coating follows)</b>						
3  wet mopping direct method	<b>Ecofloor</b> V Reshine V Antiwax forte	<b>0.5 - 1%</b> 3 - 5% 2 - 5%	<b>Micro-Mop Top/</b> Microsol mop/	<b>Socar / Drewell</b>		
3  scrubber drying direct method	<b>Ecofloor</b> V Reshine V Antiwax forte	<b>0.5 - 1%</b> 3 - 5% 2 - 5%	 <b>Microsol fibre pad/</b> S  <b>Scrubbing brush PP/</b>	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic		
3  wet scrubbing and wet vacuuming	<b>Reshine</b> Polex V Antiwax forte	<b>3 - 5%</b> 2 - 4% 2 - 5%	 <b>Microsol fibre pad/</b> S  <b>Scrubbing brush PP/</b>	<b>Monomatic LS /</b> <b>Watertank</b> <b>Duovac /</b>	heavily soiled 	
4  stain removal	See cleaning instruction no 41				if needed	
<b>cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)</b>						
5  wet mopping direct method	<b>Redur</b> F Brill F Polish	<b>3%</b> 3 - 5% 33%	<b>Flat mop/</b> Micro-Mop Top/	<b>Socar / Drewell</b>	Brill should be used with flat mop only 	
5  scrubber drying direct method	<b>Redur</b> F Brill	<b>3%</b> 3 - 5%	 <b>Microsol fibre pad/</b> S  <b>Scrubbing brush PP/</b>	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic		

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.26 Ceramic tiles, unglazed, clay paving stones, clinker brick



### maintenance cleaning

object \_\_\_\_\_

date \_\_\_\_\_



















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	 dusting damp mopping	<input type="checkbox"/>			B B Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/			
1	 dry vacuum cleaning	<input type="checkbox"/>			F S Dust roller nozzle Dust roller nozzle	Monovac / Scuba			
1	 vacuum sweeping sweeping	<input type="checkbox"/>				Speedmatic Twister Turbo Sweep	large areas: <table border="1" data-bbox="1993 646 2072 726"><tr><td>2</td></tr><tr><td>m</td></tr></table>	2	m
2									
m									
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed <table border="1" data-bbox="1993 742 2072 821"><tr><td></td></tr></table>		
									
<b>cleaning without maintenance</b>									
3	 wet mopping direct method	<input type="checkbox"/>	Ecofloor Ceratop Biosan	0.5 - 1% 0.5 - 1% 0.8 - 1.5%	Mop Microbrush/ Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix			
3	 scrubber drying direct method	<input type="checkbox"/>	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	S  Microsol fibre pad/  Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic			
<b>cleaning with maintenance</b>									
3	 wet mopping direct method	<input type="checkbox"/>	F Redur Brill	1% 1 - 2%	Mop Microbrush/ Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	Brill should be used with flat mop only 		
3	 wet mopping direct method	<input type="checkbox"/>	C Polish	10%	Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Socar / Drewell Socar / Drewell Variwet / B. Varifix	polishing with Union brush and Monomatic HS		
3	 scrubber drying direct method	<input type="checkbox"/>	F Redur Brill	1% 1 - 2%	S  Microsol fibre pad/  Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic			

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.26 Ceramic tiles, unglazed, clay paving stones, clinker brick



### interim cleaning

object \_\_\_\_\_

date \_\_\_\_\_














address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_


representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B <b>Masslinn 2000/Floorwit white</b> B Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			F <b>Dust roller nozzle</b> S Dust roller nozzle	<b>Monovac /</b> Scuba	
1	 vacuum sweeping sweeping	<input type="checkbox"/>				<b>Speedmatic Twister</b> Turbo Sweep	large areas: <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>			if needed <input type="checkbox"/>
<b>cleaning without maintenance</b>							
3	 wet mopping indirect method	<input type="checkbox"/>	<b>Reshine</b> Polex V <b>Antiwax forte</b>	<b>3 - 5%</b> 2 - 4% 2 - 5%	<b>Mop Microbrush/</b> Micro-Mop Top/	<b>Wetbox system</b> Socar / Drewell	
3	 scrubber drying indirect method	<input type="checkbox"/>	<b>Reshine</b> Polex V <b>Antiwax forte</b>	<b>3 - 5%</b> 2 - 4% 2 - 5%	 <b>Microsol fibre pad/</b> S  Scrubbing brush washbeton/ V  Scrubbing brush PP/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	
4	 wet mopping direct method	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>	<b>Micro-Mop Top/</b> Mop Microbrush/ Mop Variwet	<b>Socar / Drewell</b> Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with <input type="checkbox"/> 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**important:** For initial cleaning after interim cleaning, see "initial cleaning".

# General instructions for cleaning and care
































no.26  Ceramic tiles, unglazed, clay paving stones, clinker brick



## basic cleaning


object \_\_\_\_\_ date \_\_\_\_\_  
 address \_\_\_\_\_ customer \_\_\_\_\_  
 room classification \_\_\_\_\_ representative \_\_\_\_\_

work process: select one work stage from each number

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B <b>Masslinn 2000/Floorwit white</b> B Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			F <b>Dust roller nozzle</b> S Dust roller nozzle	<b>Monovac /</b> Scuba	
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>			if needed 
2	 damp vacuuming	<input type="checkbox"/>	F <b>pure water</b>		<b>Microsol fibre pad for edges</b>	<b>Calorvac</b>	if needed  
<b>cleaning without maintenance</b>							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Antiwax forte</b> B Remat forte C Antiwax	<b>30 - 50%</b> 10 - 20% 10 - 30%	S  <b>Microsol fibre pad/</b> S  Scrubbing brush PP/	<b>Monomatic I /</b> <b>Watertank</b> <b>Duovac /</b>	  
3	 scrubber drying indirect method	<input type="checkbox"/>	<b>Antiwax forte</b> B Remat C Antiwax	<b>30 - 50%</b> 10 - 20% 10 - 30%	S  <b>Microsol fibre pad/</b> S  Scrubbing brush PP/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	   
4	rinsing   	<input type="checkbox"/>	<b>pure water</b>		S  <b>Microsol fibre pad/</b> S  Scrubbing brush PP/	<b>Monomatic I /</b> <b>Duovac /</b> Duomatic / Laser	 
5	 stain removal	<input type="checkbox"/>	See cleaning instruction no 41				if needed
6	 wet mopping direct method	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>	<b>Micro-Mop Top/</b> Mop Microbrush/ Mop Variwet	<b>Socar / Drewell</b> Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

no.26  Ceramic tiles, unglazed, clay paving stones, clinker brick



## protective treatment

object \_\_\_\_\_

date \_\_\_\_\_












address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

cleaning method		* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping			<b>Masslinn 2000/Floorwit white</b> Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning			S <b>Dust roller nozzle</b>	<b>Monovac /</b> Scuba	
<b>pore filling (only if necessary)</b>						
2	 pore filling	F <b>Porosol</b>	<b>100%</b>	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Buket plast 22l	If necessary, one layer on porous surface  
<b>coating</b>						
3	 coating	<b>Stoner</b> Mepol HM Polish	<b>100%</b> 100% 100%	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Buket plast 22l	1 - 3 thin layers  
<b>coating</b>						
2	 impregnation	F <b>Imprasol</b>	<b>100%</b>	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Buket plast 22l	apply first layer with care  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**important:** if needed  
before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!  
Process treatment of protection: see description of method  
do not coat impregnated floors  
For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

## General instructions for cleaning and care


### no.26 Ceramic tiles, unglazed, clay paving stones, clinker brick



#### Information about the flooring




Wetrok AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrok.ch](http://www.wetrok.ch).  
Wear protection: gloves, safety goggles, work clothes  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrok.ch](http://www.wetrok.ch)  
The recommended colours of pad and brushes consist to the actual wWetrok product range  
Follow the special cleaning and care instructions of the floor manufacturer  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



#### **Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.**

Ceramic floor coverings are generally acid resistant.  
Sensitive or resistant against acid means against amidosulphuric acid  
Clinker is very hard, resistant to acid and almost waterproof.  
Unglazed clinker and clay tiles are sensitive to oil and grease.  
There must be no coating in the open air and in wet rooms. Danger of slipping!



Ceramic floor coverings are heterogeneous products made from clay and aggregates such as feldspar and fluorite.  
Terracotta tiles (cotto) are a porous earthenware slab covering.  
The higher the firing temperature and the longer the time spent in the oven, the denser and more strongly sintered the ceramic will be.  
Clinker (clay brick or earthenware flagstones) are highly fired (sintered) clay tiles.  
Scratch hardness: tiles with varying resistance to scratches, DIN 3 - 9 on the Mohs scale (satisfactory to good).



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.  
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.  
Test on an inconspicuous spot to find which product is suitable for your requirements.  
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.  
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.  
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or [academy@wetrok.ch](mailto:academy@wetrok.ch).

**Wetrok AG** Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, [info@wetrok.ch](mailto:info@wetrok.ch), [www.wetrok.ch](http://www.wetrok.ch), [www.wetrok.com](http://www.wetrok.com)