

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)
















**cleaning system with treatment
end of construction**

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning			Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /	large areas: sweeping
2  dusting damp mopping			Masslinn / Floorwit Multi squeegee/	Balit Varifix/ Balit/	
cleaning without maintenance care product (if coating follows)					
3  wet mopping direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Micro-Mop Top/ Microsol mop/	Socar / Drewell	
3  scrubber drying direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	● Pad red/ V ● Pad blue/ ● Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3  wet scrubbing and wet vacuuming	Reshine Antiwax forte V Rewit 2000	3 - 5% 2 - 5% 2 - 5%	● Pad red/ V ● Pad blue/	Monomatic I / Watertank Duovac /	heavily soiled  
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)					
4  wet mopping direct method	Redur	3%	Flat mop/ Micro-Mop Top/	Socar / Drewell	
4  scrubber drying direct method	Redur	3%	● Pad red/ ● Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
4  spray cleaning full spray	Polyspray Elfspray	100% 100%	● Pad red/ P ● Pad yellow/	Monomatic DS / Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)



maintenance cleaning

object _____

date _____















address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			Masslinn / Floorwit Synthetic fur	Balit Varifix/ Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			V Dust roller nozzle	Monovac / Scuba	large areas: sweeping
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed 
cleaning without maintenance							
3	 wet mopping direct method	<input type="checkbox"/>	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Wetbox system Socar / Dwell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V Pad red/ Pad blue/ Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
cleaning with maintenance							
3	 wet mopping direct method	<input type="checkbox"/>	Redur	1%	Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Wetbox system Socar / Dwell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	Redur	1%	V Pad red/ Pad blue/ Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	 spray cleaning partial spray	<input type="checkbox"/>	Polyspray Elfspray Stoner	100% 100% 50%	Pad red/ P Pad yellow/ P Pad Blue Ice/	Monomatic DS / Spray unit	after polishing 
3	 US spray cleaning partial spray	<input type="checkbox"/>	B US Restorer	100%	P US pad pink/ P US pad yellow/ P Pad Blue Ice/	Monomatic US / Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)



interim cleaning

object _____

date _____
























address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			Masslinn / Floorwit Synthetic fur	Balit Varifix/ Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			V Dust roller nozzle	Monovac / Scuba	large areas: sweeping
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed 
cleaning without maintenance							
3	 wet mopping indirect method	<input type="checkbox"/>	Reshine Polex Antiwax forte	3 - 5% 2 - 4% 2 - 5%	Micro-Mop Top/ Mop Microbrush/ Flat mop/	Wetbox system Socar / Drewell	 
3	 scrubber drying indirect method	<input type="checkbox"/>	Reshine Polex Antiwax forte	3 - 5% 2 - 4% 2 - 5%	V  Pad red/  Pad blue/  Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	 
cleaning with maintenance							
3	 spray cleaning full spray	<input type="checkbox"/>	Polyspray Elfspray Stoner	100% 100% 50%	 Pad red/ P  Pad yellow/ P  Pad Blue Ice/	Monomatic DS / Spray unit	after polishing 
3	 US spray cleaning full spray	<input type="checkbox"/>	B US Restorer	100%	 US pad pink/ P  US pad yellow/ P  Pad Blue Ice/	Monomatic US / Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often
For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)



basic cleaning

object _____

date _____



































address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			Masslinn / Floorwit Synthetic fur	Balit Varifix/	
1	 dry vacuum cleaning	<input type="checkbox"/>			V Dust roller nozzle	Monovac / Scuba	
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%			if needed 
3	 damp vacuuming	<input type="checkbox"/>	pure water		Microsol fibre pad for edges	Calorvac	 
cleaning without maintenance							
4	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Rewit 2000 Antiwax forte B Relino	10 - 20% 30 - 50% 20 - 50%	B  Pad green/  Pad blue/  Microsol fibre pad/	Monomatic I / Watertank Duovac /	  
4	 scrubber drying indirect method	<input type="checkbox"/>	Rewit 2000 Antiwax forte B Relino	10 - 20% 30 - 50% 20 - 50%	B  Pad green/  Pad blue/  Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	   
4	 spray cleaning full spray	<input type="checkbox"/>	Antiwax forte	30 - 50%	B  Pad green/  Pad blue/  Microsol fibre pad/	Monomatic I / Spray unit	
5	rinsing   	<input type="checkbox"/>	pure water		 Pad blue/  Microsol fibre pad/	Monomatic Duovac / Duomatic / Laser	 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

change pad often

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating

For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)



protective treatment

object _____

date _____







address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	* recommendations chemical products dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping		Masslinn / Floorwit Synthetic fur	Balit Varifix/ Balit/	
1	 dry vacuum cleaning		V Dust roller nozzle	Monovac / Scuba	
coating					
2	 coating	Mepol H 100% Mepol HM 100% Stoner 100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers  
3	 dusting damp mopping		Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	if needed

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
 Let dry protection treatment completely between the layers and before use
 do not coat impregnated floors
 Process treatment of protection: see description of method
 For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care

no.34 Synthetic resin treated industrial flooring (smooth)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Synthetic resin coverings are sensitive to organic solvents such as acetone.

Do not use solvent-based wax. Danger of slipping!
Only coat smooth, heavily used surfaces.
There must be no coating in the open air and in wet rooms. Danger of slipping!

Synthetic resin coverings consist of epoxy, polyurethane, polyester or acrylic resins, fillers and oxides.
Industrial coverings treated with synthetic resins are non-porous, pressure-resistant, mechanically loaded floor coverings with a mat or a gloss surface.
Industrial coverings treated with synthetic resins are cast or ground without joints or with expansion joints.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com