

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)

































**cleaning system without treatment
end of construction**

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1  dry vacuum cleaning			V Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /			
1  brush vacuum cleaning			S	Picojet			
1  vacuum sweeping			Carpet set - Twister	Speedmatic Twister Turbo Sweep	large areas: <table border="1" data-bbox="1989 692 2063 761"><tr><td>2 m</td></tr></table>	2 m	
2 m							
2  chewing gum removal	Karpfrost Karpotek	100%		Monovac / Scuba	if needed <table border="1" data-bbox="1989 793 2063 861"><tr><td></td></tr></table>		
							
cleaning without maintenance care product (if coating follows)							
2  wet mopping direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Micro-Mop Top/ Flat mop/	Socar / Drewell	<table border="1" data-bbox="2078 919 2168 994"><tr><td></td></tr></table>		
							
3  scrubber drying direct method	Ecofloor Reshine Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	 Microsol fibre pad/  Scrubbing brush washbeton/ V  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic			
3  wet scrubbing and wet vacuuming	Reshine Antiwax forte	3 - 5% 2 - 5%	 Microsol fibre pad/  Scrubbing brush washbeton/ V  Scrubbing brush Supernylon/	Monomatic I / Watertank Duovac /	heavily soiled <table border="1" data-bbox="1980 1120 2063 1195"><tr><td></td></tr></table> <table border="1" data-bbox="2069 1120 2152 1195"><tr><td></td></tr></table>		
							
							
4  stain removal	See cleaning instruction no 41				if needed		
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)							
5  scrubber drying direct method	Redur F Brill	3% 3 - 5%	 Microsol fibre pad/  Scrubbing brush washbeton/ V  Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic			

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)



maintenance cleaning

object _____

date _____









address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V Dust roller nozzle	Monovac / Scuba	
1	 brush vacuum cleaning	<input type="checkbox"/>			S	Picojet	
1	 vacuum sweeping	<input type="checkbox"/>			Carpet set - Twister	Speedmatic Twister Turbo Sweep	large areas: <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%		Monovac / Scuba	if needed <input type="checkbox"/>
cleaning without maintenance							
3	 wet mopping direct method	<input type="checkbox"/>	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	Ecofloor Libero Reshine	0.5 - 1% 0.5 - 3% 1 - 2%	<input checked="" type="checkbox"/> Microsol fibre pad/ V <input type="checkbox"/> Scrubbing brush washbeton/ V <input type="checkbox"/> Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
cleaning with maintenance							
3	 scrubber drying direct method	<input type="checkbox"/>	Redur F Brill	1% 1 - 2%	<input checked="" type="checkbox"/> Microsol fibre pad/ V <input type="checkbox"/> Scrubbing brush washbeton/ V <input type="checkbox"/> Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)



interim cleaning

object _____

date _____
















address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			B Dust roller nozzle Dust roller nozzle	Monovac / Scuba	
1	 brush vacuum cleaning	<input type="checkbox"/>			V	Picojet	
1	 vacuum sweeping	<input type="checkbox"/>			Carpet set - Twister	Speedmatic Twister Turbo Sweep	large areas: <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100%		Monovac / Scuba	if needed <input type="checkbox"/>
cleaning without maintenance							
3	 wet mopping indirect method	<input type="checkbox"/>	Reshine Polex G Antiwax forte	3 - 5% 2 - 4% 2 - 5%	Micro-Mop Top/ Mop Microbrush/ Flat mop/	Wetbox system Socar / Drewell	 
3	 scrubber drying indirect method	<input type="checkbox"/>	Reshine Polex G Antiwax forte	3 - 5% 2 - 4% 2 - 5%	 Microsol fibre pad/  Scrubbing brush washbeton/ V  Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	 
4	 wet mopping direct method	<input type="checkbox"/>	Biosan	3%	Mop Microbrush/ Flat mop/	Socar / Drewell Wetcar / Drewell	if needed, bad smell could be removed with <input type="checkbox"/> 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)



basic cleaning

object _____

date _____










address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 brush vacuum cleaning	<input type="checkbox"/>				Picojet	
1	 dry vacuum cleaning	<input type="checkbox"/>			V Dust roller nozzle	Monovac / Scuba	
1	 vacuum sweeping	<input type="checkbox"/>			Carpet set - Twister	Speedmatic Twister Turbo Sweep	large areas: sweeping <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	Karpotek Karpfrost	100%		Monovac / Scuba	if needed <input type="checkbox"/>
cleaning without maintenance							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Antiwax forte G Rewit 2000 B Remat forte	30 - 50% 10 - 20% 10 - 20%	<input checked="" type="checkbox"/> Microsol fibre pad/ <input type="checkbox"/> Scrubbing brush washbeton/ V <input type="checkbox"/> Scrubbing brush Supernylon/	Monomatic I / Watertank Duovac /	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
3	 scrubber drying indirect method	<input type="checkbox"/>	Antiwax forte G Rewit 2000 B Remat	30 - 50% 10 - 20% 10 - 20%	<input checked="" type="checkbox"/> Microsol fibre pad/ <input type="checkbox"/> Scrubbing brush washbeton/ V <input type="checkbox"/> Scrubbing brush Supernylon/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
4	rinsing 	<input type="checkbox"/>	pure water		<input checked="" type="checkbox"/> Microsol fibre pad/ <input type="checkbox"/> Scrubbing brush washbeton/ <input type="checkbox"/> Scrubbing brush Supernylon/	Monomatic I / Duovac / Duomatic / Laser	<input type="checkbox"/> pH 7 <input type="checkbox"/>
5	 stain removal	<input type="checkbox"/>	See cleaning instruction no 41				if needed
6	 wet mopping direct method	<input type="checkbox"/>	Biosan	3%	Mop Microbrush/ Flat mop/	Socar / Drewell Wetcar / Drewell	if needed, bad smell could be removed with <input type="checkbox"/> <input type="checkbox"/>

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)



protective treatment

object _____

date _____








address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning			B Dust roller nozzle	Monovac / Twinvac /	
pore filling (only if necessary)						
2	 pore filling	F Porosol	100%	Florfix/ Flat mop/	Florfix/ Drewell/	If necessary, one layer on porous surface  
coating						
3	 coating	Stoner Mepol HM	100% 100%	Florfix/ Flat mop/	Florfix/ Drewell/	1 - 3 thin layers  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: if needed
 before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
 Process treatment of protection: see description of method
 For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care

no.39 Cement surface layer (smooth and coated)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Do not coat structured floor coverings.

Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solenhofer stone, travertine, slate or sandstone is sensitive to acid.

Soft stone is sensitive to scratches, only use suitable pads and brushes.

Plastic-bonded synthetic stone is sensitive to solvents.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!



Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.

Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Cast stone is laid as plates and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.