

# General instructions for cleaning and care

## no.59 Linoleum (antistatic)
























**cleaning system without treatment  
end of construction**

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning			<b>Dust roller nozzle</b> Neverclog filter without ring Filter bag with ring	<b>Twinvac /</b> Duovac / Silento /	large areas: sweeping
2  dusting damp mopping			<b>Masslinn 2000/Floorwit white</b> Multi squeegee/	<b>Balit Varifix/</b> Balit/	
<b>cleaning without maintenance care product (if coating follows)</b>					
3  wet mopping direct method	<b>Ecofloor</b> V Antiwax forte	<b>0.5 - 1%</b> 2 - 5%	<b>Micro-Mop Top/</b> Microsol mop/	<b>Socar / Drewell</b>	
3  scrubber drying direct method	<b>Ecofloor</b> V Antiwax forte	<b>0.5 - 1%</b> 2 - 5%	 <b>Pad red/</b>  <b>Pad blue/</b>	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	
3  wet scrubbing and wet vacuuming	<b>Antiwax forte</b>	<b>2 - 5%</b>	 <b>Pad blue/</b>  <b>Pad red/</b>	<b>Monomatic I /</b> <b>Watertank</b> <b>Duovac /</b>	 
<b>cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)</b>					
4  wet mopping direct method	<b>Redur</b>	<b>3%</b>	<b>Micro-Mop Top/</b> Microsol mop/	<b>Socar / Drewell</b>	
4  scrubber drying direct method	<b>Redur</b>	<b>3%</b>	 <b>Pad red/</b>  <b>Pad blue/</b>	<b>Duomatic /</b> Mambo / Samba Sprinter / iMatic	
4  spray cleaning full spray	<b>Polyspray</b>	<b>100%</b>	 <b>Pad red/</b> P  <b>Pad yellow/</b>	<b>Monomatic DS /</b> <b>Spray unit</b>	after polishing 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**comments** e.g. spot removal and basic cleaning with protective treatment  
When spray cleaning, you should change your pad often

# General instructions for cleaning and care

## no.59 Linoleum (antistatic)



### maintenance cleaning

object \_\_\_\_\_

date \_\_\_\_\_

























address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			<b>Masslinn / Floorwit</b> Synthetic fur	<b>Balit Varifix/</b> Balit/	
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>			if needed 
<b>cleaning without maintenance</b>							
3	 wet mopping direct method	<input type="checkbox"/>	<b>Ecofloor</b> F Alcosal V Antiwax forte	<b>0.5 - 1%</b> 1 - 2% 0.5 - 1%	<b>Micro-Mop Top/</b> Mop Microbrush/ Mop Variwet	<b>Wetbox system</b> Socar / Drewell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	<b>Ecofloor</b> Libero V Antiwax forte	<b>0.5 - 1%</b> 0.5 - 3% 0.5 - 1%	B  <b>Pad red/</b> F  <b>Pad blue/</b> S  <b>Microsol fibre pad/</b>	<b>Duomatic /</b> Mambo / Samba Sprinter / iMatic	
3	 polishing, vacuum polishing	<input type="checkbox"/>			B  <b>US pad yellow/</b> F  <b>Pad Blue Ice/</b> C  <b>Microsol fibre pad/</b>	<b>Monomatic US /</b> <b>Suction ring</b> Monomatic HS /	after polishing 
<b>cleaning with maintenance</b>							
3	 wet mopping direct method	<input type="checkbox"/>	<b>Redur</b>	<b>1%</b>	<b>Micro-Mop Top/</b> Mop Variwet	<b>Wetbox system</b> Socar / Drewell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	<b>Redur</b>	<b>1%</b>	B  <b>Pad red/</b> F  <b>Pad blue/</b> S  <b>Microsol fibre pad/</b>	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	
3	 spray cleaning partial spray	<input type="checkbox"/>	<b>Polyspray</b>	<b>100%</b>	P  <b>Pad red/</b>  <b>Pad yellow/</b>	<b>Monomatic DS /</b> <b>Spray unit</b>	after polishing 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**important:** When spray cleaning, you should change your pad often

# General instructions for cleaning and care

## no.59 Linoleum (antistatic)



### interim cleaning

object \_\_\_\_\_

date \_\_\_\_\_
















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			<b>Masslinn / Floorwit</b> Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			V <b>Dust roller nozzle</b>	<b>Monovac /</b> Scuba	large areas: sweeping
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>			if needed 
<b>cleaning without maintenance</b>							
3	 wet mopping indirect method	<input type="checkbox"/>	V <b>Polex</b> Antiwax forte	<b>2 - 4%</b> <b>2 - 5%</b>	<b>Micro-Mop Top/</b> Mop Microbrush/	<b>Wetbox system</b> Socar / Drewell	
3	 scrubber drying indirect method	<input type="checkbox"/>	V <b>Polex</b> Antiwax forte	<b>2 - 4%</b> <b>2 - 5%</b>	B  <b>Pad red/</b>  <b>Pad blue/</b> F  <b>Microsol fibre pad/</b>	<b>Duomatic / Laser</b> Sprinter / iMatic Mambo / Samba	
<b>cleaning with maintenance</b>							
3	 spray cleaning full spray	<input type="checkbox"/>	<b>Polyspray</b>	<b>100%</b>	P  <b>Pad red/</b>  <b>Pad yellow/</b>	<b>Monomatic DS /</b> <b>Spray unit</b>	after polishing 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**important:** When spray cleaning, you should change your pad often  
For initial cleaning after interim cleaning, see "initial cleaning".

# General instructions for cleaning and care

## no.59 Linoleum (antistatic)



### basic cleaning

object \_\_\_\_\_

date \_\_\_\_\_






























address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting  damp mopping	<input type="checkbox"/>			<b>Masslinn / Floorwit</b> Synthetic fur	<b>Balit Varifix/ Balit/</b>	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S <b>Dust roller nozzle</b> Dust roller nozzle	<b>Monovac / Scuba</b>	
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	100%			if needed 
<b>cleaning without maintenance</b>							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Relino</b> Antiwax forte	20 - 50% 30 - 50%	B  <b>Pad blue/</b>  <b>Pad green/</b>	<b>Monomatic I / Watertank</b> <b>Duovac /</b>	heavily soiled   
3	 scrubber drying direct method	<input type="checkbox"/>	<b>Relino</b> Antiwax forte	20 - 50% 30 - 50%	B  <b>Pad blue/</b>  <b>Pad green/</b>	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	   
3	 spray cleaning full spray	<input type="checkbox"/>	<b>Antiwax forte</b>	30 - 50%	B  <b>Pad green/</b>  <b>Pad green/</b>	<b>Monomatic I / Spray unit</b> Monomatic LS /	
4	Spülen   	<input type="checkbox"/>	<b>pure water</b>		 <b>Pad blue/</b>  <b>Microsol fibre pad/</b>	<b>Monomatic I / Duovac / Duomatic / Laser</b>	large areas: scrubber-dryer  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

### important:

change pad often

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating

## General instructions for cleaning and care


### no.59 Linoleum (antistatic)



#### Information about the flooring



Wetrot AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrot.ch](http://www.wetrot.ch).  
Wear protection: gloves, safety goggles, work clothes  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrot.ch](http://www.wetrot.ch)  
The recommended colours of pad and brushes consist to the actual wWetrot product range  
Follow the special cleaning and care instructions of the floor manufacturer  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



**Strong alkalines can destroy or discolour linoleum coverings. Use a special basic linoleum cleaner!**  
**Linoleum coverings are sensitive to abrasive pads and brushes.**

Linoleum coverings are largely insensitive to acids, fats, oils and solvents.  
Certain manufacturers give linoleum coverings a surface finish at the factory (first maintenance).



Linoleum is a 100% natural product consisting of linseed oil, wood and cork flour, resins, colorants and limestone on a jute underlay.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: crater can be removed with the fingers.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.  
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.  
Test on an inconspicuous spot to find which product is suitable for your requirements.  
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.  
Dirt-trapping zones, incl. dirt-trapping mats (Wetrot Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.  
For training courses, contact the Wetrot Academy, tel. +41 (0)43 255 51 43 or [academy@wetrot.ch](mailto:academy@wetrot.ch).

**Wetrot AG** Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, [info@wetrot.ch](mailto:info@wetrot.ch), [www.wetrot.ch](http://www.wetrot.ch), [www.wetrot.com](http://www.wetrot.com)