




Product data sheet Imprasol

V 02 / 14.07.2016

Wetrok Imprasol

Sealing



Recommended dosage:



Undiluted

Benefits:

Protects absorbent natural and cast stone surfaces from deep soiling and prevents water staining.
Improves cleanability of the treated surface.

Application:

For sealing porous natural and cast stone in areas protected from the weather (clay tiles, sandstone, marble, clinker, slate, etc.).

Please note:

Wetrok Imprasol can slightly alter surface colours. For this reason, test the seal first on a section that is not obviously visible.
Not suitable for water and damp-sensitive floor coverings, for outdoor areas or wet zones.

Properties:

Milky white fluid
Consumption: 20 – 50 g/m²

pH value of concentrate:

Not applicable

Important ingredients:

Hydrophobic compounds, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Shelf life (unopened): 24 months.

Recommended application methods:

Strongly absorbent surfaces

The floor must be free of all previous coatings and must be completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply Wetrok Imprasol using application device or mop device and cotton-wool mop over the entire surface. The product must soak in. Wipe off excess product. Drying time min. 24 h.

Low absorbent surfaces

The floor must be free of all previous coatings and must be completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply Wetrok Imprasol in sections on the floor covering using the spray method. Use a single-brush machine and red pad to work it in uniformly until the surface is free of any excess product. Leave the floor covering to dry out completely (at least 24h). Check the sealant effect using a water test. Repeat sealing process if necessary.