

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wetrok Karspray**

Revision date: 31.03.2016

Product code: 282

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Wetrok Karspray

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Washing and cleaning products (including solvent based products)  
Restricted to professional users.

**1.3. Details of the supplier of the safety data sheet**

Company name: Wetrok AG  
Headquarter  
Street: Steinackerstr. 62  
Place: CH-8302 Kloten, Switzerland  
Telephone: +41 (0)43 255 51 51  
e-mail: chemie@wetrok.ch  
Contact person: Head Regulatory Telephone: +41 (0)43 255 53 50  
Internet: www.wetrok.ch  
Responsible Department: BU Chemicals / Regulatory  
Mobile + 41 (0)79 657 45 20

**1.4. Emergency telephone number:**

+41 44 251 51 51 (Tel. 145) (Toxikologisches Zentrum)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:  
Flammable gas: Flam. Gas 1  
Gases under pressure: Liquefied gas  
Acute toxicity: Acute Tox. 4  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Hazardous to the aquatic environment: Aquatic Chronic 2  
Hazard Statements:  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes serious eye irritation.  
Causes skin irritation.  
Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 2 of 8

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

#### Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

#### 2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
90622-57-4	C10-C12, Isoalkanes			30 - < 100 %
	923-037-2		01-2119471991-29	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411			
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether			20 - < 30 %
	225-878-4	603-052-00-8		
	Eye Irrit. 2, Skin Irrit. 2; H319 H315			
74-98-6	propane			15 - < 20 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			5 - < 10 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
142-82-5	heptane; n-heptane			5 - < 10 %
	205-563-8	601-008-00-2		
	Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H225 H304 H315 H336 H400 H410			
106-97-8	butane			5 - < 10 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 3 of 8

#### Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

##### After inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

##### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

##### After ingestion

Rinse mouth immediately and drink plenty of water.

#### 4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date. In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

May produce an allergic reaction. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water. Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.

#### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

##### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion hazard.

#### 6.3. Methods and material for containment and cleaning up

Ventilate affected area.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 4 of 8

#### 6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes. Observe instructions for use. Use only in well-ventilated areas.

##### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Protect against direct sunlight. Store in a cool dry place. Recommended storage temperature: at room temperature

##### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

##### Further information on storage conditions

Minimum storage temperature: 15°C

Maximum storage temperature: 25°C

#### 7.3. Specific end use(s)

Notice the directions for use on the label.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

##### Eye/face protection

Tightly sealed safety glasses. Eye-pieces out of plastic.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 5 of 8

specific working place concentration and quantity of hazardous substances.

Recommendation:

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material 0.4 mm

Breakthrough time (maximum wearing time) 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn DIN EN 374

#### Skin protection

Only wear fitting, comfortable and clean protective clothing.

#### Respiratory protection

Respiratory protection necessary at: insufficient ventilation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid Aerosol
Colour:	colourless
Odour:	Solvent

#### Test method

pH-Value: not applicable

#### Changes in the physical state

Initial boiling point and boiling range: -44 °C

Flash point: -97 °C

Lower explosion limits: 0.6 vol. %

Upper explosion limits: 9.5 vol. %

Ignition temperature: 215 °C

Density: 0.785 g/cm<sup>3</sup>

Water solubility: insoluble

### 9.2. Other information

none

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Ignition hazard.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

This article doesn't contain dangerous substances or preparations intended to be released under normal or reasonably foreseeable conditions of use.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Wetrok Karspray**

Revision date: 31.03.2016

Product code: 282

Page 6 of 8

**SECTION 11: Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

Based on available data, the classification criteria are not met.

**Irritation and corrosivity**

Causes serious eye irritation.

Causes skin irritation.

Irritating to eyes. After skin contact: Irritant.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification according to Regulation (EC) No. 1272/2008 [CLP] The product has not been tested.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
142-82-5	heptane; n-heptane					
	Acute fish toxicity	LC50	375 mg/l	96 h	GESTIS	

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

No information available.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
142-82-5	heptane; n-heptane	4,66
106-97-8	butane	2,89
75-28-5	isobutane	2,8

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

There are no data available on the mixture itself.

**Further information**

Do not allow to enter into surface water or drains.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 7 of 8

Classification according to Regulation (EC) No. 1272/2008 [CLP] The product has not been tested.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Transport category: 2  
 Tunnel restriction code: D

#### Other applicable information (land transport)

E0

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



## SECTION 15: Regulatory information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Wetrok Karspray

Revision date: 31.03.2016

Product code: 282

Page 8 of 8

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

##### Additional information

aerosol directive (75/324/EEC).

##### National regulatory information

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s):

1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

For industrial purposes only. Notice the directions for use on the label. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*