



Product data sheet Ketovapor CIP 3 Chlor

V 02 / 26.07.2016



Wetrok Ketovapor CIP 3 Chlor

Industrial CIP cleaner



Recommended dosage (in cold water):



Industrial CIP cleaning
0.1 l – 0.3 l / 10 l

Benefits:

Specially developed for CIP (cleaning in place) systems in the pharma and cosmetic industries, and in food processing operations.
For removing animal and vegetable fat/oil/grease, starch, protein.

Application:

For cleaning washable and alkali-resistant surfaces (stainless steel, plastic, ceramic tiles, etc.).
Suitable for use in ultrasonic units and automatic washers with spray nozzles.

Please note:

Wetrok Ketovapor CIP 3 Chlor is not suitable for alkali-sensitive surfaces (aluminium, enamel, etc.).
Do not put product into contact with acids!

Properties:

Low lather
Highly alkaline
Non-perfumed
Contains chlorine

pH value of concentrate:



Important ingredients:

Base compounds, chelating agent, chlorine-based bleach

Storage/shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Shelf life (unopened): 24 months.

Recommended application methods:

Cleaning in Place

Follow the operating instructions for the CIP system. Rinse the system with water. Spray in cleaning solution, making sure that it is circulating well. Allow to work in for a short period and then rinse thoroughly with water.