




Product data sheet Mepol 2000

V 02 / 13.07.2016

Wetrok Mepol 2000

Coating



Recommended dosage:



Protective treatment
Undiluted

Benefits:

Environmentally friendly, protective treatment free of metal salts.

Application:

For treating hard and elastic floor coverings (PVC, linoleum, natural and cast stone, etc.).

Please note:

Shake well before use!

Not suitable for water and damp-sensitive floor coverings, for outdoor areas or wet zones.

Treat porous floor coverings with Porosol before use.

Properties:

Polymer/wax-based

Silk finish to high-shine

Water vapor diffusion guaranteed

Protection product free from heavy metals

Environmentally friendly due to the absence of metal salts and fluoropolymers

pH value of concentrate:



Important ingredients:

Polymers, wax, alkali-soluble resins, solvents, surfactants, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

Recommended application methods:

Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings. Allow at least 60 min. drying time between coatings. If required, polish with soft pad once fully dry (after 2 to 3 days).