



Product data sheet Mepol HX

V 02 / 13.07.2016

Wetrok Mepol HX

Coating



Recommended dosage:



Protective treatment
Undiluted

Benefits:

Protective treatment for non-slip floor coverings according to DIN 18032. Resistant to a wide range of alcohol-based hand disinfectants.

Application:

For treating hard and elastic floor coverings (PVC, linoleum, natural and cast stone, etc.).

Please note:

Shake well before use!

Not suitable for water and damp-sensitive floor coverings, for outdoor areas or wet zones.

Treat porous floor coverings with Wetrok Porosol before use.

Properties:

Polymer/wax-based

DIN 18032 - high tread safety

High-shine finish

Water vapour diffusion guaranteed

Forms a polishable, water-resistant protective film

pH value of concentrate:



Important ingredients:

Polymers, wax, solvents, surfactants, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

Recommended application methods:

Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings. Allow at least 60 min. drying time between coatings. If required, polish with soft pad once fully dry (after 2 to 3 days).