




Product data sheet Porosol

V 02 / 14.07.2016

Wetrok Porosol

Pore filler



Benefits:

Seals pores to protect them from water and moisture-resistant floor coverings, thus improving the cleaning capacity of the surface. Long-life effect.

Application:

For sealing all porous surfaces in areas protected from the weather (natural and cast stone, asphalt, hard concrete, coarse ceramic, magnesite, linoleum, etc.).


Please note:

Wetrok Porosol reduces drying times on treated floors as well as reducing consumption of coating materials on older linoleum floors. Not suitable for water and damp-sensitive floor coverings.

Properties:

Milky white fluid
Not water-soluble
Water vapor diffusion guaranteed
Consumption: 25 - 50 g/m²

pH value of concentrate:



Recommended dosage:



Undiluted

Important ingredients:

Polymers, wax, solvents, surfactants, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place. Protect from frost. Keep container closed when not in use. Shelf life (unopened): 24 months.

Recommended application methods:

Filling pores

The floor must be free of all previous coatings and must be completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply Wetrok Imprasol using application tool or mop device and cotton-wool mop over the entire surface. The product must soak in. Wipe off excess product. Drying time min. 24 h. Important: Check the sealant effect using a water test. Treat floor coverings with Wetrok Mepol.