



Product data sheet Antiwax

V 02 / 06.07.2016

wetrok[®]

Wetrok Antiwax

Basic and industrial cleaners



Recommended dosage (in cold water):



Maintenance cleaning
0.05 l – 0.1 l / 10 l



Intermediate cleaning
0.2 l – 0.5 l / 10 l



Basic cleaning
2 l / 10 l

Wax removal
1 l – 3 l / 10 l

Benefits:

High-performance basic and industrial cleaner.
Ideal for removing oil, grease and industrial soiling.
Suitable for removing protective films (wax coatings).

Application:

For cleaning washable and alkali-resistant surfaces and floor coverings (PVC, natural and cast stone, clinker, natural rubber, etc.).


Please note:

Use Wetrok Antiwax in a maximum 5% solution on linoleum.
With concentrations above 10% rinse afterwards with water.

Properties:

Low lather
Slightly alkaline
Non-perfumed

pH value of concentrate:



Important ingredients:

Surfactants, solvents, soap

Storage/shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Shelf life (unopened): 24 Months.

Recommended application methods:

Wet mopping (by hand)

Dust mop or dry vacuum the floor surface to remove dust. Soak mop with cleaning solution, wring out well and wet mop floor covering.

Scrub drying

Fill up the fresh water tank with the cleaning solution. Remove any loose dirt, and dust mop or dry vacuum the floor. Scrub dry the floor covering thoroughly with a scrubber-drier and suitable pad or brush.

Basic cleaning

Remove any loose dirt, and dust mop or dry vacuum the floor. Apply the basic cleaning solution to the surface, leave to act for 15 minutes without allowing to dry out! Wet scrub with a single-brush machine / automatic scrubber and a suitable pad or brush. Leave the solution to act for 10 minutes. Do not allow to dry out! Vacuum up the dissolved coating or soiling. Then rinse the floor covering well with clean water (up to approx. pH 7).