



Product data sheet Karpex

V 02 / 14.07.2016



Wetrok Karpex

Carpet cleaners



Benefits:

Extra-high-performance basic and intermediate cleaner for synthetic carpets. Can be used both with spray extraction and with carpet pad method.

Application:

For basic and intermediate cleaning of textile floor coverings.


Please note:

Wetrok Karpex is not suitable for carpets made of wool, mixed fibres or other alkaline-sensitive materials. In case of any doubt, use Wetrok Retex. Spray extraction: only carpets with synthetic (non water-sensitive) base weave and water-resistant adhesives / substrate.

Properties:

Low lather
Slightly alkaline
Lightly perfumed
Without brighteners

pH value of concentrate:



Important ingredients:

Surfactants, solvents, chelating agent, polymers, fragrance

Storage/shelf life:

Store in original container in a cool, well-ventilated place. Protect from frost. Keep container closed when not in use. Shelf life (unopened): 24 months.

Recommended dosage (in cold water):



Carpet pad method
0.1 l – 0.3 l / 10 l



Spray extraction (direct)
0.1 l – 0.3 l / 10 l



Spray extraction (indirect)
0.3 l – 1 l / 10 l

Recommended application methods:

Carpet pad method

Dry or brush vacuum the textile floor covering. Remove any staining using Wetrok Karpothek. Spray cleaning solution onto textile floor covering and carpet pad and begin cleaning using circular movements of the single brush machine. Work in sections. Turn over or replace soiled pads. Brush the carpet pile with a pile brush and allow the covering to dry completely.

Carpet extraction

Dry or brush vacuum the textile floor covering. Pre-treat any stains with Wetrok Karpothek. **Direct:** Pour cleaning solution into the water tank and perform spray extraction on the floor in a single work process. Brush the carpet pile with a pile brush and allow the covering to dry completely (min. 24h). **Indirect:** Spray floor covering with cleaning solution and leave to act for approx. 10 minutes. Do not allow to dry out! Perform spray extraction on the covering using clean water. Brush the carpet pile with a pile brush and allow the covering to dry completely (min. 24h).