




## Product data sheet Leinol NW

V 02 / 13.07.2016

# Wetrok Leinol NW

## Wood treatment oil



### Application:

For the care and maintenance of planed and oiled wooden floors.

### Please note:

Shake well before use!

There is the risk that textiles which come into contact with the product could catch fire when drying.

Untreated wooden floors should first be treated with Wetrok Leinol BW.

### Properties:

Aqueous linseed oil emulsion

Matt to satin finish

Free of highly volatile solvents

### pH value of concentrate:



### Important ingredients:

Linseed oil, polymers, wax, surfactants

### Recommended dosage:



**Maintenance cleaning**  
Undiluted

### Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

### Recommended application methods:

#### Protective treatment

The floor must be free of any earlier treatment and completely dry. Dust mop or dry vacuum the floor covering. Apply Wetrok Leinol NW in sections in 1 to 2 thin coatings. Remove excess oil with a multi squeegee. Leave to soak in for at least 3 hours. Work in the surface oil with a single-brush machine and a red pad. If you require a light gloss finish, polish using a single-brush machine and soft pad after full hardening (after at least 24 h).