




## Product data sheet Mepol HM

V 02 / 13.07.2016

# Wetrok Mepol HM

## Coating



### Recommended dosage:



**Protective treatment**  
Undiluted

### Benefits:

Satin-finish protective treatment.

### Application:

For treating hard and elastic floor coverings (PVC, linoleum, natural and cast stone, etc.).

### Please note:

Shake well before use!

Not suitable for water and damp-sensitive floor coverings, for outdoor areas or wet zones.

Treat porous floor coverings with Wetrok Porosol before use.

### Properties:


Polymer/wax-based

Matt to satin finish

Water vapour diffusion guaranteed

Forms a polishable, water-resistant protective film

### pH value of concentrate:



### Important ingredients:

Polymers, wax, solvents, surfactants, preservatives

### Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

### Recommended application methods:

#### Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings.

Allow at least 60 min. drying time between coatings.

If required, polish with soft pad once fully dry (after 2 to 3 days).