



Product data sheet Polish

V 02 / 13.07.2016



Wetrok Polish

Coating



Benefits:

The protective treatment specially designed for wood.

Application:

For treating wood and wood-type floor coverings (parquet, cork, urphen, magnesite, etc.).

Please note:

Shake well before use!

Wetrok Polish is not suitable for outdoor areas or wet zones.

Properties:

Polymer/wax-based

Matt to satin finish

Water vapor diffusion guaranteed

Forms a polishable, water-resistant protective film

Lightly perfumed

pH value of concentrate:



Recommended dosage (in cold water):



Protective treatment
Undiluted



Spray cleaning
3 l / 10 l

Important ingredients:

Polymers, wax, alkali-soluble resins, solvents, surfactants, fragrance, preservatives.

Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

Recommended application methods:

Spray cleaning (using cleaner machine)

Remove any loose dirt, and dust mop or dry vacuum the floor. Spray on cleaning solution and work it in immediately with a single-brush machine and red pad. Reverse or replace dirty pads when worn out.

Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings. Allow at least 60 min. drying time between coatings. If required, polish with soft pad once fully dry (after 2 to 3 days).