



## Product data sheet Remat forte

V 02 / 06.07.2016

# Wetrok Remat forte

Basic and industrial cleaners



## Benefits:

Extremely high-performance maintenance cleaner.  
For removal of polymer and wax coatings.  
Good at removing encrustations.

## Application:

For mechanical cleaning of washable and alkali-resistant floor coverings (PVC, natural and cast stone, clinker, etc.).

## Please note:

Not suitable for linoleum, natural rubber, wooden flooring, asphalt or painted surfaces.

Use Wetrok Remat Forte Dosage at a max. 20% concentration for polished cast stone, epoxy and PU coverings.

## Properties:

Low lather  
Highly alkaline  
Contains solvents  
Non-perfumed

## Recommended dosage (in cold water):



**Intermediate cleaning**  
0.1 l – 0.5 l / 10 l




**Basic cleaning**  
1 l – 2 l / 10 l



**Crust removal**  
2 l / 10 l

## pH value of concentrate:



## Important ingredients:

Surfactants, solvents, base compounds, soap

## Storage/shelf life:

Store in original container in a cool, well-ventilated place.  
Protect from frost. Keep container closed when not in use.  
Shelf life (unopened): 24 months.

## Recommended application methods:

### Basic cleaning

Remove any loose dirt, and dust mop or dry vacuum the floor. Apply the basic cleaning solution to the surface, leave to act for 15 minutes without allowing to dry out! Wet scrub with a single-brush machine / automatic scrubber and a suitable pad or brush. Leave the solution to act for 10 minutes. Do not allow to dry out! Vacuum up the dissolved coating or soiling. Then rinse the floor covering well with clean water (up to approx. pH 7).